



Decking and Sealer Products Since 1923

Crack Filler

Technical Bulletin



Desert Brand Crack Filler is an excellent filler for many types of surfaces. It can be used in patching and resurfacing of masonry, wood, roofing, brick, metal, firewalls, flashing, gutters, deck, stucco, nonglazed tile, trailer tops, skylights, chimneys, and vents. It is a ready to use formulation whose tough and flexible properties make it an excellent bridging compound for interior and exterior use. It is a flexible, water resistant material, which expands and contracts with movement to reduce further cracking.

FEATURES:

- Interior and primed exterior use.
- Cures to hard but flexible smooth finish.
- Superior adhesion and cohesive strength when surface is properly prepared.
- Does not degrade or brittle with age like oil-based products.
- Non-flammable.
- All you need is soap and water for cleanup.

CLEAN SURFACE:

- Surface must be dry and free of grease, oil, dirt, wax, polish or other foreign matter.
- Dull glossy surfaces by sanding.

APPLICATION:

- Apply as is. No mixing or thinning required.
- Fill hole or crack using putty knife. Deep cracks may require additional fillings.
- Smooth surface to desired finish while material is still workable.
- Product is not meant to be sanded.
- It may be primed and painted when dry.
- Crack filler can be tinted with universal colorants but mixing would be difficult due to paste consistency.
- Allow to dry overnight when application is less than 1/8" thick.
- Drying times are dependent on temperature, humidity, and application thickness.

PRECAUTIONS:

- It is not recommended to apply when the temperature is below 50°F.
- Do not allow Crack Filler to freeze, it will not thaw to a usable product.
- Close container after each use.
- Use with adequate ventilation.
- Wear dust mask when sanding.
- Keep out of reach of children.
- Do not take internally.

The information in this technical bulletin is based on data obtained by our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data, the results to be obtained from the use thereof, or that any such use will not infringe any patent. This information is furnished upon the condition that the person receiving it shall make his own tests to determine the suitability thereof for his particular purpose. Sales specifications, although current at time of publication, are subject to change due to process improvements. For latest product specifications, contact our nearest sales office.

TECHNICAL DATA

Data	Crack Filler
Color in container:	Off White
VOC (g/L):	<50 g/L-0.4 lbs/gal
Typical Solids (wt.%):	75%
Typical Density (lbs/gal):	12.43
Viscosity (cps):	45,000 ±1,000

Storage:	Cool dry place. Do not allow to freeze.
Shelf Life:	12 months in unopened container.
Packaging:	1 quart and 1 gallon containers

For additional information, please refer to Safety Data Sheet (SDS).

CLEANING OF EQUIPMENT:

- Immediately clean equipment and hands with soapy warm water.
- Dry material can be removed from equipment with lacquer thinner, follow manufacturer's precautions.
- Disposal of any unused material must comply with local, state, and federal regulations.

Manufactured by

HILL BROTHERS *Chemical Co.*

800.994.8801

LOCATIONS:

City of Industry - San Jose, CA
Phoenix - Tucson, AZ • Salt Lake City, UT

© Hill Brothers Chemical 2020