



Decking and Sealer Products Since 1923

Paver Sealer

Technical Bulletin



Desert Brand Paver Sealer is a high-performance acrylic/urethane clear sealer developed specifically for porous paver tiles and other porous masonry surfaces. Paver Sealer is an interior/exterior sealer formulated to enhance and provide maximum durability and protection of porous paver tiles; thereby, providing a deep penetrating, non-yellowing, scuff resistant finish. The sealer is not recommended for non-porous or dense surfaces.

CLEAN SURFACE:

- Make sure surface is free of grease, oil, dirt, wax, polish or other foreign matter.

PREPARE SURFACE:

- Make certain that the bond to any previously applied stain or sealer is secure.
- On newly installed tile, allow 24 to 48 hours for grout joints to dry thoroughly before applying.
- Apply a small amount of sealer to test for possible lifting.

APPLICATION:

- Stir contents thoroughly.
- Use a fine textured sponge, brush, roller, or with spray equipment.
- Apply as is. Do not dilute.
- Apply an even coating when surface temperature is between 55° and 85°F.

DOUBLE UP:

- Two or more applications may be necessary to achieve maximum abrasion and stain resistant qualities.
- Two or more coats may be necessary depending upon surface porosity and desired finish.
- Allow 2 to 3 hours between coats.
- Drying and recoat times are dependent on temperature, humidity and film thickness.

PRECAUTIONS:

- Foot traffic should remain off of the sealed surface for 24 hours.
- For heavy foot traffic allow 72 hours for proper curing.
- Protect the sealed tile floor from excessive and prolonged exposure to foods and greases.

MAINTENANCE:

- For additional scuff resistance use Desert Brand Top Finish.

CLEANING OF EQUIPMENT:

- Equipment and hands may be cleaned with mild liquid detergent and warm water.
- Dry material can be removed with lacquer thinner, follow manufacturer's precautions.
- Disposal of any unused material must comply with local, state, and federal regulations.

The information in this technical bulletin is based on data obtained by our own research and is considered accurate. However, no warranty is expressed or implied regarding the accuracy of these data, the results to be obtained from the use thereof, or that any such use will not infringe any patent. This information is furnished upon the condition that the person receiving it shall make his own tests to determine the suitability thereof for his particular purpose. Sales specifications, although current at time of publication, are subject to change due to process improvements. For latest product specifications, contact our nearest sales office.

TECHNICAL DATA

<u>Data</u>	<u>Paver Sealer</u>
Color in Container:	Milky white (dries clear)
VOC (mg/L):	<100
Typical Solids (%):	21%
Volume Solids (%):	19%
Typical Density (lbs/gal):	8.5 lbs./gal
Chemical Resistance:	24 hrs under watch glass
<hr/>	
Coverage (Average sq. ft., per coat @ 1mil):	200-300
<i>Coverage rates are dependent on surface conditions and application techniques.</i>	
<hr/>	
ASTM D3359	5
<i>Test measuring adhesion.</i>	
<hr/>	
Storage:	Cool dry place. Do not allow to freeze.
Shelf Life:	12 months in unopened container
Packaging:	1, 5 and 55 gallon containers

For additional information, please refer to Safety Data Sheet (SDS).

For maintenance information, please refer to Desert Brand Technical Bulletin TB141: Maintenance and Care of Desert Brand Sealers.

Warning – Like any quality finish, Paver Sealer reduces the porosity of the surface being sealed. Be aware that oil, water, mud, or other materials on a sealed walkway can make the surface slippery. Good house-keeping and maintenance are important, proper drainage is imperative.

Manufactured by
HILL BROTHERS *Chemical Co.*
800.994.8801
1675 N. Main St • Orange, CA 92867
LOCATIONS:
City of Industry • San Jose, CA
Phoenix • Tucson, AZ • Salt Lake City, UT
© Hill Brothers Chemical 2019