

FASTER INSTALL. BETTER VALUE.

BRENNAN | CC003

Construction	Ultimate Flex LVT
Installation Method	Glue Down
Thickness	2mm
Wear Layer	10 Mil Ultra Spill & Stain Guard
Plank Size	6" W x 48" L
Sq. Ft./Carton	48
Cartons/Pallet	70
Warranty	15 YR Limited Residential, 6 YR Limited Light Commercial



COLOR SHOWN: TRADEWINDS



WATERPROOF



NO ACCLIMATION*



MADE IN THE USA



BLEACHED CANYON
AM709



RIVERWOOD
AM740



TRADEWINDS
AM792



HONEYSUCKLE
SC734



MAGNOLIA
SC737



SILVER SPRINGS
SC795

PERFORMANCE ACCESSORIES

INVENTORY STYLE NUMBER	DESCRIPTION	SPREAD RATE
MVONE.40.4GAL.GL M	MOHAWK V-ONE - 4 GAL	350 SF/GAL †
MVONE.10.1GAL.GL M	MOHAWK V-ONE - 1 GAL	350 SF/GAL †
XL23	MOHAWK PRIME COAT - 4 GAL	315-360 SF/GAL

* For details, see installation and warranty information at mohawkflooring.com

† With 1/16" x 1/16" x 1/32" U-notch trowel

TESTING INFORMATION

ASTM 1303	Type 1, Grade 3
ASTM F1914 Residual Indentation	0.05 Passes
ASTM C1028-96 Static Coefficient of Friction	Dry 0.72 / Wet 0.48 Passes
ASTM E492-09 Sound Transmission / Impact Insulation	Class IIC 55
ASTM E648-08 Radiant Flux of Floor Covering	Class 1 Passes
ASTM E662 Smoke Density (flaming & non-flaming)	Passes 450 or less
ASTM F137 Flexibility	5mm Passes
ASTM 2199 Dimensional Stability	Passes
ASTM F925 Resistance to Chemicals	Very Good
ASTM F1514 Resistance to Heat	Passes
ASTM F1514 Resistance to Light	Passes



Resilient



Stain Resistant



Easy to Clean



Approved for Any Level



High Variation



SCS Certified

