



# FAIRWINDS

SHEET VINYL



MOHAWK



## SPECIFICATIONS

Construction .....	Sheet Vinyl	Width .....	12'
Recommended Usage .....	Residential	Standard length .....	85 LF
Thickness .....	140 Gauge	Warranty .....	Limited 7-Year Residential
Wear Layer .....	8 mil InvisiCare™		

## TESTING INFORMATION

EN 13501 Inflammability .....	BFL - S1
DIN 51130 / EN 13893 Slip Resistance .....	R9 / DS
EN 423 Resistance to Chemicals .....	Very Good
EN 12524 Underfloor Heating .....	Suitable
ASTM E648 & E662 Fire Test .....	N/A
ASTM F137 Flexibility .....	10 mm Passes
ASTM F970 Residual Indentation .....	0.014
ASTM F925 Resistance to Chemicals .....	No Change
ASTM F1514 Resistance to Heat .....	Passes
ASTM F1514 Resistance to Light .....	Passes

## ADHESIVES AND SEAM SEALER

Style	Description	Spread Rate
VA65A Adhesive	Mohawk M640 - 4 gallon	300 sqf/gallon*
VA65A Adhesive	Mohawk M640 - 1 gallon	300 sqf/gallon*
M7A Seam Sealer	Mohawk M7 - 8 ounce	100 LF with 1/8" bead
M7A Seam Sealer	Mohawk M7 - 1 quart	400 LF with 1/8" bead
XL23A Primer	Mohawk Prime Coat - 4 gallon	315-360 sf/gallon

\*with 3/8" short nap paint roller

## WOOD VISUALS



**UMBER**  
FAL24-T865  
47.24" x 39.37"  
Drop: 23.62"



**JAVA**  
FAL24-T2345  
47.24" x 39.37"  
Drop: 23.62"



**SILVER STRAND**  
FAL24-MC791  
39.37" x 39.17"  
Drop: 19.69"



**MOUNTAIN GREY**  
FAL24-TV796  
39.37" x 39.17"  
Drop: 19.69"



**CARAVEL BROWN**  
FAL24-TV786  
39.37" x 39.17"  
Drop: 19.69"



**MESA TAN**  
FAL24-TV737  
39.37" x 39.17"  
Drop: 19.69"



## TILE VISUALS



**CLAY**  
FAL24-T930  
39.37" x 39.37"  
No Drop



**OTTERTAIL**  
FAL24-T994  
39.37" x 39.37"  
Drop: 13.11"



**CLOUDY SKY**  
FAL24-RC590  
78.74" x 39.37"  
Drop: 19.69"




**FOSSIL**  
FAL24-RC573  
78.74" x 39.37"  
Drop: 19.69"



**DARK ASH**  
FAL24-RC546  
78.74" x 39.37"  
Drop: 19.69"



**STONEY CREEK**  
FAL24-RC532  
78.74" x 39.37"  
Drop: 19.69"



**FIELDSTONE**  
FAL24-CT595  
39.37" x 39.37"  
No Drop



**GREY GRANITE**  
FAL24-CT590  
39.37" x 39.37"  
No Drop

