

VERSATILITY FOR EVERYDAY LIFE

SPECIFICATIONS

VERSATECH Ultra

Style.....	M542V
Thickness.....	3.0 MM
Wear Layer.....	15 mil Ultra Spill & Stain Guard
Roll Width.....	13'2"
Installation Method.....	Glue Down
Warranty.....	Limited Lifetime Residential 10-YR Limited Light Commercial

VERSATECH Plus

Style.....	M184V
Thickness.....	2.5 MM
Wear Layer.....	12 mil Spill & Stain Guard
Roll Width.....	13'2"
Installation Method.....	Glue Down
Warranty.....	20-YR Limited Residential 5-YR Limited Light Commercial

VERSATECH

Style.....	M178V
Thickness.....	2.0 MM
Wear Layer.....	10 mil Spill & Stain Guard
Roll Width.....	13'2"
Installation Method.....	Glue Down
Warranty.....	10-YR Limited Residential



WATERPROOF



SEAMLESS



RESILIENT



ROASTED MOCHA | 858
47.24" x 39.37" w/ 23.62" drop



MOTH GREY | 892B
47.24" x 39.37" w/ 23.62" drop



ALMOND LATTE | 891
47.24" x 39.37" w/ 23.62" drop



BLAZING AUTUMN | 756
47.24" x 39.37" w/ 23.62" drop



LUNAR SURFACE | 745
47.24" x 39.37" w/ 23.62" drop



COTTAGE WHITE | 757
47.24" x 39.37" w/ 23.62" drop



DARK ASH | W94
47.24" x 78.74" w/ 23.62" drop



HAZE | 890
47.24" x 78.74" w/ 23.62" drop



MERINO | 593A
47.24" x 39.37" w/ 23.62" drop



BATTLESHIP GREY | 875
47.24" x 39.37" w/ 23.62" drop



NATURAL TWINE | 841
47.24" x 39.37" w/ 23.62" drop



BLUE METAL | 896
39.37" x 39.37" w/ 19.69" drop



NOMADIC BRONZE | 835
39.37" x 39.37" w/ 19.69" drop



LYRIC BLUE | 591T
47.24" x 78.74" w/ 23.62" drop



CYPRESS GREY | 595T
47.24" x 78.74" w/ 23.62" drop



THRESHOLD TAUPE | 832
47.24" x 78.74" w/ 23.62" drop



MOONLIT ORCHID | 845
47.24" x 78.74" w/ 23.62" drop



HIGH TEA | 892A
47.24" x 78.74" w/ 23.62" drop



ATHENA | 590N
78.74" x 39.37" w/ no drop



ECLIPSE | 595N
78.74" x 39.37" w/ no drop



UBER UMBER | 545
78.74" x 39.37" w/ no drop



SEDATE GREY | 593W
39.37" x 39.37" w/ 23.62" drop



CALL IT MELLOW | 544
39.37" x 39.37" w/ 23.62" drop



NOCTURNE | 999
39.37" x 39.37" w/ 13.11" drop



HOMESTAR BROWN | 943
39.37" x 39.37" w/ 13.11" drop



SAMOAN SANDS | 932W
39.37" x 39.37" w/ 13.11" drop



BEN DAVIS GREY | 991W
39.37" x 39.37" w/ 39.37" drop



GRISISITO | 594T
78.74" x 39.37" w/ 39.37" drop



IVORY BLACK | 597T
78.74" x 39.37" w/ 39.37" drop



SABLE | 945
39.37" x 39.37" w/ 26.25" drop



SAND TROPEZ | 932D
39.37" x 39.37" w/ 26.25" drop



WOLF GREY | 910
39.37" x 39.37" w/ 26.25" drop



RIVERWAY | 594F
39.37" x 39.37" w/ 19.69" drop



DUSK | 599
39.37" x 39.37" w/ 19.69" drop



PARAMOUNT | 594A
47.24" x 39.37" w/ 23.62" drop



WARM SIENNA | v
47.24" x 39.37" w/ 23.62" drop



STERLING | 596
39.37" x 39.37" w/ 13.12" drop



EVENING HUSH | 597L
39.37" x 39.37" w/ 13.12" drop




GOLD ORCHID | 533
39.37" x 39.37" w/ 19.69" drop



DURANGO BLUE | 572
39.37" x 39.37" w/ 19.69" drop



GREY AREA | 593M
39.37" x 39.37" w/ 19.69" drop




SUEDE GREY | 595M
39.37" x 39.37" w/ 19.69" drop



BROWN SUGAR | 998
39.37" x 39.37" w/ 19.69" drop



RICHMOND GOLD | 991A
39.37" x 39.37" w/ 19.69" drop



CALIENTE | 978
47.24" x 78.74" w/ 47.24" drop



OCEAN FLOOR | 992
47.24" x 78.74" w/ 47.24" drop




GREYS HARBOR | 594E
39.37" x 39.37" w/ 19.69" drop




JONQUIL | 534E
39.37" x 39.37" w/ 19.69" drop



SKYFALL | 573E
39.37" x 39.37" w/ 19.69" drop



CITYSCAPE | 597Z
39.37" x 39.37" w/ 19.69" drop



MYSTICAL BLACK | 598Z
47.24" x 39.37" w/ 23.62" drop



REFLECTION | 534Z
47.24" x 39.37" w/ 23.62" drop

TESTING INFORMATION

Versatech

ASTM F137 Flexibility	10 mm Passes
ASTM F970 Residual Indentation	0.012
ASTM F925 Resistance to Chemicals	Very Good
ASTM F1514 Resistance to Heat	Passes
ASTM F1514 Resistance to Light	Passes

Versatech Plus

ASTM E492 IIC Sound Transmission	IIC 58
ASTM F137 Flexibility	10 mm Passes
ASTM F970 Residual Indentation	0.010
ASTM F925 Resistance to Chemicals	Very Good
ASTM F1514 Resistance to Heat	Passes
ASTM F1514 Resistance to Light	Passes

Versatech Ultra

ASTM E492 IIC Sound Transmission	IIC 60
ASTM F137 Flexibility	10 mm Passes
ASTM F970 Residual Indentation	0.006
ASTM F925 Resistance to Chemicals	Very Good
ASTM F1514 Resistance to Heat	Passes
ASTM F1514 Resistance to Light	Passes

ADHESIVES & SEAM SEALER

INVENTORY STYLE NUMBER	DESCRIPTION	SPREAD RATE
MVONE.40.4GAL.GL M	MOHAWK V-ONE - 4 GAL	350 SF/GAL*
MVONE.10.1GAL.GL M	MOHAWK V-ONE - 1 GAL	350 SF/GAL*
M7	MOHAWK M7 - 8OZ	100 LF W/ 1/8" BEAD
XL23	MOHAWK PRIME COAT - 4 GAL	315-360 SF/GAL

*with 3/8" short nap paint roller

