





26104 Calendar



26105 Datebook



26301 Research



26302 Directory




26303 Memo




26406 Contacts



26407 Files




26508 Time




26509 Server



26510 Tasks



26700 Data



26803 Folder




26702 Photo Album

Style Name	SYNC UP	
Style Number	J0126	
Product Type	Carpet Tile	
Construction	Graphic Loop	
Fiber	100% Eco Solution Q100™ Nylon	
Dye Method	SOLUTION DYED /SPACE DYED	
Primary Backing	Synthetic	
Secondary Backing	Ecoworx	
Traffic Rating	Heavy	
Protective Treatments	SSP Protective Treatments	
	U.S.	Metric
Product Size	24 in x 24 in	60.96 cm x 60.96 cm
Area Per Carton	48 ft <sup>2</sup>	4.46 m <sup>2</sup>
Pieces Per Carton	12	
Gauge	1/10 in	39.37 per 10 cm
Stitches	10 per in	39 per 10 cm
Finished Pile Thickness	0.108 in	2.74 mm
Average Density	7333 oz/yd <sup>3</sup>	11.27
Total Thickness	0.278 in	7.06 mm
Tufted Weight	22 oz/yd <sup>2</sup>	745.9 g/m <sup>2</sup>
GSA Approved Product	11.27	



## Recommended Installation Methods



1/4 Turn

## Performance Testing

Pill Test	<b>Pass</b>
Radiant Panel	<b>Class I</b>
NBS Smoke	<b>Less than 450</b>
Electrostatic Propensity	<b>Less than 3.5 kv</b>
CRI Greenlabel Plus	<b>GLP9968</b>
ADA Compliance	<b>&gt;0.6, meets the recommended static coefficient of friction for ADA walking surfaces and accessible routes</b>

Test Reports may be included or listed by the manufacturing/inventory style number as opposed to the noted selling style number.

## Warranties

**Carpet Tile Lifetime Commercial Limited Warranty**

## Environmental

Recycled Content **Pre-consumer - 35%, Post-consumer - 0%**

Specifications are subject to nominal manufacturing variance. Material supply and/or manufacturing processes may necessitate changes without notice.